

U-630 Advanced


Universal Machining Centre



www.spinner.eu.com sales@spinner.eu.com

Machine Highlights

Available in 3 configurations U3-630: 3-axes-version with fixed table U4-630: 4-axes-version with large rotary table U5-630: 5-axes-version with integrated rotary/tilting table




All versions available as U-1530 with enlarged X stroke


Ergonomic Universal Dynamic Highly precise Productive 5-axes simultaneous machining


Machine Highlights

U3-630 [Fixed table]



U4-630 [Rotary table]





All versions with modern linear guides on rigid cast construction







Clamping table U4-630 Clamping surface on both sides

Technical data


| Working area | U3-630 | U4-630 | U5-630 |
|--|---|---|----------------|
| X axis | 630 mm | | |
| Y axis | 530 mm | | |
| Z axis | 465 mm | | |
| Table | | | |
| Table dimensions | 920 x 540 mm | 410 x 610 mm ¹⁾ / Ø 560 mm ²⁾ | Ø 650 / 500 mm |
| Max. table load | 750 kg | 400 kg | 500 kg |
| T-slots | 18H8 | 14H8 | 18H8 |
| Axes | | | |
| Feed / rapide traverse | 48 m/min | | |
| Number of simultaneously interpolated axes | 3 (4) | 4 | 4 (5) |
| Spindle | | | |
| Max. speed | 12.000/15.000 rpm (SK40), 20.000 rpm (HSK63) | | |
| Performance P _{max} | 12.000/15.000: 25 kW; 20.000: 28 kW | | |
| Torque M _{max} | 12.000/15.000: 135 Nm; 20.000: 100 Nm | | |
| Tool magazine | | | |
| Number of tool stations | 32 (optional 54 / 122) | | |
| Max. tool diameter | 76 mm | | |
| In case of free adjacent tool stations | 130 mm ³⁾ | | |
| Max. tool length | 300 mm | | |
| Max. tool weight | 7 kg | | |
| General indications | | | |
| Dimensions (L x W x H) 4) | 2745 x 2420 x 2820 mm | | |
| Weight ⁵⁾ | ~ 5.500 - 7.100 kg (according to the equipment) | | |

1) Clamping table, 2) Rotary table, 3) Valid for spindle speed up to 1 2.000 rpm, toolholder limited to 80 mm in case of spindle speeds >12.000 rpm; 4) See floorplan, 5) Machine net weight





U630-Advanced



U630-Advanced

-305

C

Y axis 0-530

225

0

占

凸

X axis 0-630

шш


8


B axis -90°


Ĕ Ä

Ш

B axis +110°







Compact dimensions for low space requirement

Version with standard chip conveyor

SPINNER Werkzeugmaschinenfabrik GmbH





Spinner Machine-Tools are working successfully world wide with many well known clients in more than 60 countries on 6 continents.We have been fortunate enough to attract small component suppliers in addition to well known global groups in all metal machining industries.

We have designed and produced the most modern machine-tools since 1950. More than 20.000 delivered machines demonstrate their high efficiency, precision and reliability, everyday.

Although Spinner is a medium-sized enterprise we produce and sell more than 1.000 CNC machines a year. And the number is increasing every year. Our company combines the know-how of a global player with the flexibility and cost-effective structures of a family owned business.

Place your trust in our products as well and let us know what we can do for you.



www.spinner.eu.com

SPINNER Werkzeugmaschinenfabrik GmbH

Rudolf-Diesel-Ring 24 82054 Sauerlach Tel. +49 (0) 8104 803-0 Fax +49 (0) 8104 803-19 sales@spinner.eu.com



Version 26.8.2015

Technical changes of specifications and pictures are subject to change without notice - Pictures can include options, accessories