



TECHNICAL SPECS

MAX WORK SIZE mm (in)	Φ330 × H320 (Φ12.99 × H12.60) Φ420 × H320 (Φ16.54 × H12.60) *with conditions Φ330 × H300 (Φ12.99 × H11.81) - PC10
WORKING SURFACE mm (in)	Φ250 (Φ9.84) - Standard Φ250 (Φ9.84) + Table through - Option 6port
LOADING CAPACITY kg (lb)	80 (176.37)
TOOL TAPER	CAT #40/BT - Standard HSK-A63 - Option
NUMBER OF TOOLS	30 : BT40 - Standard 60 : BT40 - Standard 90 : BT40 - Option
SPINDLE SPEED RPM	15,000 : BT40 - Standard 15,000 PowerUp : BT40 - Option 20,000 : BT40 - Option
TRAVEL (X/Y/Z) mm (in)	435/465/560 (17.13/18.31/22.05)
TRAVEL (A/C) °	-125~+10/360
RAPID TRAVERSE (X/Y/Z) m/min (ipm)	40 (1,574.80)
RAPID TRAVERSE (A/C) min ⁻¹	17/33
NC SYSTEM	Matsura G-Tech 31i
INDUSTRIES	Automotive and High Performance, Die / Mold, Medical