



### TECHNICAL SPECS

|   |  |
|---|--|
| <b>MAX WORK SIZE</b> mm (in)                  | <p>Φ850 × H450 ( Φ33.46 × H13.77 )</p> <p>Φ850 × H385 ( Φ33.46 × H13.77 ) *with pallet option</p>              |
| <b>WORKING SURFACE</b> mm (in)                | <p>Φ500 ( Φ19.68 ) - Standard</p> <p>Φ700 ( Φ27.56 ) - Option</p> <p>Φ500 ( Φ19.68 ) + Flat Table - Option</p> |
| <b>LOADING CAPACITY</b> kg (lb)               | <p>500 ( 1,102 ) - Standard</p> <p>400 ( 882 ) - Option</p>  |
| <b>TOOL TAPER</b>                             | <p>CAT #40/BT - Standard</p> <p>HSK-A63 - Option</p>   |
| <b>NUMBER OF TOOLS</b>                        | <p>90 : BT40 - Standard</p> <p>120 : BT40 - Option</p>   |
| <b>SPINDLE SPEED</b> RPM                      | <p>12,000 : BT40 - Standard</p> <p>15,000 : BT40 - Option</p> <p>20,000 : BT40 - Option</p>                    |
| <b>TRAVEL (X/Y/Z)</b> mm (in)                 | 900/780/650 ( 35.43/30.70/25.59 )  |
| <b>TRAVEL (A/C)</b> °                         | -125~+30/360   |
| <b>RAPID TRAVERSE (X/Y/Z)</b> m/min (ipm)     | 40 ( 1,574.80 )  |
| <b>RAPID TRAVERSE (A/C)</b> min <sup>-1</sup> | 17/33  |
| <b>NC SYSTEM</b>                              | Matsuura G-Tech 31i  |
| <b>INDUSTRIES</b>                             | Aerospace and Defense, Automotive and High Performance,<br>Die / Mold, Medical, Oil and Energy                 |